

Galvanized Steel

Rough Bore Metal Hose

Packed or Unpacked galvanized steel unlined hose available in .010 to .030 thicknesses. Used where a more economical hose is required.

Applications

- Exhaust Systems • Conduit • Spouts
- Casing • Dry Bulk Product Transfer

Temperature - Low/High	- 40°F to +400°F
Abrasion - Interior/Exterior	Good/Good
Flexibility	Medium Flexibility
Pressure	Low 5psi Unpacked / 15psi Packed
Chemical	Good
Standard Length	25' Feet
Size - ID	1.25" inch ID to 16" inch ID



Packing Key

GT = Gas Tight
 AP = Apyrous Filament
 CC = Cotton Cord
 SS = Stainless Steel
 SIL = Silicone
 CPR = Copper

Temperature

GT Packing:	-20° to 180°F	(Neg. 20 in. HG)	(Pos 20 P.S.I.)
AP Packing:	-40° to 400°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
CC Packing:	-60° to 300°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
SS Packing:	-60° to 1800°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
SIL Packing:	-65° to 500°F	(Neg. 20 in. HG)	(Pos 20 P.S.I.)
CPR Packing:	-40° to 500°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
Unpacked:	-60° to 1800°F	(No pressure rating)	

R-200-G .010" Strip Thickness

Diameter	Part #	Bend Radius (Inches)	Hose Weight (Lbs./Foot)
1.25	10033	5.5	0.42
1.50	12204	6.8	0.49
1.75	12205	7.0	0.57
2.00	10035	7.5	0.64
2.25	12206	7.8	0.72
2.50	10038	8.5	0.80
2.75	12207	9.2	0.87
3.00	10040	10.0	0.95
3.50	10045	10.5	1.10
4.00	10049	14.5	1.40
4.50	10052	16.3	1.50
5.00	10053	18.0	1.70
6.00	10056	21.8	2.00