

# Medium Duty Aluminized Steel —

## Rough Bore Metal Hose

Packed or Unpacked aluminized steel unlined hose available in .018 thickness. Used where a more economical hose is required.

### Applications

- Exhaust Systems • Conduit • Spouts
- Casing • Dry Bulk Product Transfer

Temperature - Low/High	- 40°F to +850°F
Abrasion - Interior/Exterior	Good/Good
Flexibility	Medium Flexibility
Pressure	Low 5psi Unpacked / 15psi Packed
Chemical	Excellent
Standard Length	25'
Size - ID	3" to 10" ID

### **R-360-AS** **.018" Strip Thickness**

Diameter	Part #	Bend Radius (Inches)	Hose Weight (Lbs./Foot)
3.00	12784	14.0	1.82
3.50	12785	15.5	2.11
4.00	12786	16.5	2.40
4.50	12787	18.0	2.70
5.00	12788	20.0	2.99
6.00	12789	26.0	3.57
7.00	12790	27.0	4.16
8.00	12791	27.5	4.64
10.00	12792	28.0	5.78

Consult factory for additional sizes.



### Packing Key

GT = Gas Tight  
 AP = Apyrous Filament  
 CC = Cotton Cord  
 SS = Stainless Steel  
 SIL = Silicone  
 CPR = Copper

	Temperature		
GT Packing:	-20° to 180°F	(Neg. 20 in. HG)	(Pos 20 P.S.I.)
AP Packing:	-40° to 400°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
CC Packing:	-60° to 300°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
SS Packing:	-60° to 1800°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
SIL Packing:	-65° to 500°F	(Neg. 20 in. HG)	(Pos 20 P.S.I.)
CPR Packing:	-40° to 500°F	(Neg. 15 in. HG)	(Pos 15 P.S.I.)
Unpacked:	-60° to 1800°F	(No pressure rating)	