



SPECIFICATIONS (Weights and bend diameters are based on extended hose and are approximate)

Hose Size I. D. (Inches)	Series and Strip Thickness									
	HT3008A .007" - .008" Aluminum		HT3006S .005" - .006" AL29-4-C SS		HT3007S .006" - .007" SS		HT2150S .014" - .016"		HT2200S .018" - .020" SS	
	Minimum Inside Bend Dia. (Inches)	Weight per foot (lbs.)	Minimum Inside Bend Dia. (Inches)	Weight per foot (lbs.)	Minimum Inside Bend Dia. (Inches)	Weight per foot (lbs.)	Minimum Inside Bend Dia. (Inches)	Weight per foot (lbs.)	Minimum Inside Bend Dia. (Inches)	Weight per foot (lbs.)
3	4.5	.15	6.0	.35	6.0	.40	21.0	1.40	22.0	2.00
3½	5.2	.17	7.0	.40	7.0	.45	24.0	1.60	25.0	2.30
4	6.0	.20	8.0	.45	8.0	.50	27.0	1.80	29.0	2.60
4½	6.8	.22	9.0	.50	9.0	.58	30.0	2.00	32.0	2.80
5	7.5	.25	10.0	.55	10.0	.63	32.0	2.30	34.0	3.00
5½	8.2	.27	11.0	.60	11.0	.70	37.0	2.50	39.0	3.30
6	9.0	.28	12.0	.65	12.0	.75	42.0	2.70	44.0	3.60
7	10.5	.33	14.0	.75	14.0	.86	46.0	3.20	50.0	4.20
8	12.0	.38	16.0	.85	16.0	1.00	52.0	3.60	56.0	4.70
9	13.5	.40	18.0	1.00	18.0	1.15	56.5	4.05	61.0	5.30
10	15.0	.45	20.0	1.10	20.0	1.27	61.0	4.50	65.0	5.90
12	18.0	.54	24.0	1.30	24.0	1.50	72.0	5.40	76.0	7.00
14	21.0	.63	28.0	1.50	28.0	1.73	100.0	6.30	106.0	8.10
16	24.0	.72	32.0	1.75	32.0	2.00	—	—	121.0	9.20
18	27.0	.81	36.0	2.00	36.0	2.30	—	—	☎	☎
20	30.0	.90	40.0	2.20	40.0	2.50	—	—	☎	☎
22	33.0	1.00	44.0	2.42	44.0	2.75	—	—	☎	☎
24	36.0	1.10	48.0	2.64	48.0	3.00	—	—	☎	☎

NOTE: Standard lengths are 25 ft. **extended**; Cut lengths available on request.

☎ Telephone factory for availability.