

Rubber Fab Technologies Group's X-TREME FLEX

RFXF- Smoothbore with Convoluted Hose Flexibility



Half the Minimum Bend Radius of
Conventional Smoothbore Fluoropolymer

Features:

- Smoothbore PFA Fluoropolymer lined hose
- Superior Flexibility
- Superior Kink Resistance
- Full Vacuum Rated
- Stainless Steel Reinforced
- -65°F to 325°F Operating temperature
- Advanced design serves as a thermal insulator to the touch
- Available sizes 3/8" I.D. to 1-1/2" I.D.

Applications:

- Food & Beverage Processing
- Chemical Transfer
- Pharmaceutical processing
- Hot CIP Solutions

Approvals:

- 3A Sanitary Standard
- FDA 21 CFR 177.1550
- U.S.P. Class VI

FLEXIBILITY at the X-TREME

TUBE:

Smoothbore PFA Tube

REINFORCEMENT:

Bonded Wire Braid
Silicone
Textile Braided Composite

COVER:

Stainless Steel Braid

Part #	I.D.	O.D.	Working Pressure @ 68F	Vacuum Rating	Bend Radius inches
06RFXF	.375	.625	300	29.9	2.00
08RFXF	.500	.755	300	29.9	2.50
12RFXF	.750	1.04	250	29.9	3.00
16RFXF	1.00	1.29	250	29.9	4.00
24RFXF	1.50	1.85	200	29.9	7.00

RUBBER FAB

