

# BioLector® I

## 48 Parallel Microbioreactors

m2p  
labs

High-Throughput  
Real-Time Monitoring  
Scalability  
Automation



# High Information Content for fast Selection

## BioLector® I


The BioLector® I is the first bench top microfermentation system to perform high-throughput fermentations together with online monitoring of the most common fermentation parameters (biomass, pH, DO and fluorescent molecules).

The system is based on a standard microtiter plate format and operates with non-invasive, optical sensors. Due to the continuous and rigorous shaking during the optical measurements and over the whole experimental time it is ideally suited for aerobic and anaerobic cultures. For the first time, real time culture monitoring at a massive parallel scale becomes possible!

## Applications

- Cell line and strain screening
- Media screening and optimization
- Fermentation parameter optimization
- Anaerobic and microaerophilic fermentations
- Synthetic and systems biology
- Statistical design of experiments (DoE)
- Growth characterization
- Protein building kinetics
- High-throughput protein expression
- Enzyme and cell activity tests
- Functional genomics
- Proteomic studies
- Inhibition and toxicity tests
- Quality control

## Measurements



Multiparameter-Monitoring in the FlowerPlate®  
48 well FlowerPlate®, 1000 µL, 800 rpm, 37 °C

# 48 Parallel Microbioreactors



## Features


### Online Parameters

- Biomass concentration
- pH-value
- Dissolved oxygen (DO)
- NAD(P)H and riboflavins
- Fluorescent molecules (GFP, YFP, DsRed ...)

### System Performance

- Working volume of 800 – 2400  $\mu\text{L}$
- 48 parallel microreactions
- No foaming problems
- Broad range of  $k_L a$  values (25 – 600 1/h)
- Continuous gas exchange and oxygen supply
- Equal power input to each reactor
- Defined engineering parameters and scalability
- Controlled gas atmosphere ( $\text{CO}_2$ ,  $\text{O}_2$  and  $\text{N}_2$ )
- Humidity control (> 75 % rH)
- Temperature control (20 – 50  $^{\circ}\text{C}$ )

## Operating Principle



Multiparameter FlowerPlate® with Optodes



# Smaller and Smarter

m2p  
labs




BioLector® | m2p-labs

## Advantages

- Real time kinetics out of 48 parallel fermentations
- Microfermentation in standard MTP format
- High-throughput and easy automation
- Broad linear range for biomass (up to 100 g/L CDW, 600 OD)
- Excellent reproducibility (CV < 5 %)
- No edge effects
- Continuous shaking operation (no artifacts)
- Defined mass transfer conditions (no O<sub>2</sub>-limitation)
- Easy scale up to lab-fermenters
- Industry leading data analysis software
- Fast and easy data analysis included
- A valuable tool for PAT and QbD

## Intelligent Software



Data Analysis with the BioLector Software

# Technical Specifications

## BioLector® I

### SYSTEM

**Art.-No. G-BL-100**

Operation conditions	
Plate format	48
Volume	800 – 2400 µL (depending on microtiter plate)
Temperature	5 °C below room temperature, max. 50 °C
Gas atmosphere	Only air (optional modules, see below)
Humidity	> 75 % rH
Orbital shaker	400 – 1500 rpm at 3 mm (diameter)

Modules	
Dimensions (W × H × D)	795 mm × 333 mm × 470 mm
Weight	Approx. 40 kg
Power source	100 – 240 V (50/60 HZ)
Interface	Ethernet
Ambient conditions	15 – 40 °C, max. 75 % rH
Automation	Optionally, the BioLector® can be integrated into the RoboLector® liquid handling systems*

Optical measurements	
Filter configuration	up to 6 different filters
Wavelengths	365 nm – 800 nm
MTP read time	down to 3 min/parameter/48 wells
Linear range of cell counts	0.2 – 600 OD (0.1 – 100g/L CDW)

pH / DO Monitoring	
Calibration	Precalibrated plates
Measurement range pH	3.0 – 6.0 or 4.5 – 7.5 depending on plate type
Measurement range DO	0 – 100 % oxygen saturation
Application mode	Disposable technology

### OPTIONAL MODULES

Art.-No.	Module description	Application	Additional feature	Note
<b>E-AN-200</b>	BL-Module for anaerobic cultivation	Strict anaerobic fermentation + small, controlled gas flow	Gassing with pure N <sub>2</sub> or CO <sub>2</sub> or other defined gases, controlled gas flow through mass flow controller (1 – 10 mL/min)	
<b>E-02-100</b>	O <sub>2</sub> -upregulation module	Fermentation with O <sub>2</sub> enriched air	Control of gas atmosphere: 21 – 35 % O <sub>2</sub>	Only one O <sub>2</sub> sensor can be installed in the device
<b>E-02-25</b>	O <sub>2</sub> -downregulation module	Fermentation at O <sub>2</sub> reduced air, microaerophilic conditions	Control of gas atmosphere: 2 – 21 % O <sub>2</sub>	Only one O <sub>2</sub> sensor can be installed in the device
<b>E-CO2-10</b>	CO <sub>2</sub> -upregulation module	Fermentation with CO <sub>2</sub> controlled gas atmosphere	Control of gas atmosphere: 0 – 10 % CO <sub>2</sub>	
<b>E-AN-201</b>	BL-Preparation: anaerobic cultivation	Preparation for later addition of anaerobic module		Easy integration of anaerobic module on site
<b>E-AN-202</b>	Anaerobic cultivation set	Later addition of: Strict anaerobic fermentation + small, controlled gas flow	Gassing with pure N <sub>2</sub> or CO <sub>2</sub> or other defined gases	Anaerobic module for integration on site
<b>E-FRET-100</b>	BL-Option for FRET measurement	FRET measurements in BioLector® (1 × excitation / 2 × emission fluorescences)	Additional measurement of a second, synchronous emission wavelength	Two photomultipliers installed
<b>E-OP-101-199</b>	LED/Filter Module	Measurement of additional fluorescences in the BioLector®	Measurement at additional wavelengths	Ask your sales manager for available modules
<b>E-OP-900</b>	Notebook for BioLector® System	Notebook for data analysis	Data analysis and visualization on a separate computer	

It is possible to combine all types of modules (AN, O<sub>2</sub>, CO<sub>2</sub>, FRET) in one device.

### ORDERING

**Leasing option available**
**EUROPE** +49-2401-805-330  
order@m2p-labs.com

**USA** +1-631-501-1878  
orderUS@m2p-labs.com

# The Company

## m2p-labs is a worldwide leading supplier of microbioreactors.

The company focuses on microreaction and automated solutions for screening and bioprocess development. The microfermentation technology enables customers to conduct experiments with greater efficiency, better quality and lower cost than in any other cultivation platform. More knowledge from small scale leads to more rational and reliable decisions in the development of bioprocesses.



## PRODUCT PORTFOLIO

### EUROPE

m2p-labs GmbH  
Arnold-Sommerfeld-Ring 2  
52499 Baesweiler  
Germany  
Phone +49-2401-805-330  
Fax +49-2401-805-333  
info@m2p-labs.com

### USA

m2p-labs, Inc.  
400 Oser Ave, Suite 1650  
Hauppauge, NY 11788  
USA  
Phone +1-631-501-1878  
Fax +1-631-501-1060  
infoUS@m2p-labs.com

### Systems

The BioLector® microbioreactor is a unique high-throughput fermentation system. In up to 48 parallel cultures the essential fermentation parameters such as biomass concentration, pH and DO as well as fluorescent proteins or substrates can be all monitored online. The advanced BioLector® Pro technology is using proprietary microtiter plates with an integrated microfluidic chip. By using the microfluidic technology the system continuously controls the pH of each culture individually as well as the feeding for fed-batch cultivations. The BioLector® microbioreactors are established systems for bacterial, yeast, fungi, plant and insect cells. All systems are suitable for aerobic, microaerophilic and strict anaerobic cultivations.

### Disposables

m2p-labs provides worldwide unique microtiter plates with improved oxygen transfer and excellent mixing properties. Due to its design, the FlowerPlate® supplies microbial cultures even with high oxygen demands with a sufficient amount of oxygen. In addition, the proprietary microfluidic plate uses 16 donor wells for online feeding and pH control. The round well plate delivers moderate oxygen transfer for organisms with lower demand in oxygen or organisms sensitive to shear stress. All plates are available with different optical sensors for different applications.

### Automation

The RoboLector® provides an unique automated cultivation platform combining the high-throughput fermentation and the online monitoring capability of the BioLector® with the very accurate and reproducible pipetting of a liquid handling robot. The system is used for media preparations, automated sampling and dosing steps, inductions and fed-batch processing.

[www.m2p-labs.com](http://www.m2p-labs.com)

Information is subject to change. m2p-labs, BioLector, FlowerPlate and RoboLector are registered trademarks of m2p-labs GmbH, Germany.

Tel.: +52 (55) 6273-4046 / 6273-4047 / 2465-1016