# **ZenPure**


## Band Clamp SS Filter Housing Multi-Round

#### Band Clamp Filter Housing Vessels

are designed for industrial and commercial applications. Vessels are constructed of 304 or 316 stainless steel and accept DOE, 222/FLAT, and 222/FIN end cartridges in 10", 20", 30" & 40" nominal lengths.

#### Features:

- Single o-ring design (Buna-N standard)
- Easy-access self-centering heavy-duty band-clamp closure
- 316 stainless steel universal seal cups and compression plates allow vessels to accept D OE , -222/FLAT, or -222/FIN-end cartridges
- 304 & 316 stainless steel construction
- Poly-coat finish (exterior only)
- 150 PSI pressure rating
- Heavy-duty welded mounting/support legs
- 316 stainless steel cap/spring assemblies and v-posts



#### Materials of Construction

Housing: 316/ 304 Stainless Steel Clamp: 304 Stainless Steel Cap Spring: 316L SS O-Rings: Buna N

Dimensions (nominal) Lengths (in): 10, 20, 30 and 40

<u>Connections - Offset</u> Inlet/Outlet : Tri Clamp, Flange, FNPT Vent/Drain : FNPT

Finish

Interior: 2B finish

Exterior: PolyCoat Operating Conditions

Max operating pressure: 150 psi (10bar)

#### **Band Clamp Filter Housing Ordering Guide**

ZenPure and PureFlo are registered trademarks of ZenPure Corporation or an affiliated company

Copyright 2003-2012 ZenPure or an affiliated company. All rights reserved

Construction	Number of Filters	Length	Inlet/Outlet Fitting Size	· ·	Outlet Configurations	Material of Construction	Pressure Rating	Interior / Exterior Finish
	<b>4</b> = 4 Filters	<b>1</b> =10"	<b>2</b> = 2"	F = RF Flange	2 = Opposite Side	<b>4</b> = 304SS	<b>15</b> = 150 PSI	PC = Poly-Coat
GTCHB = Band	5 = 5 Filters	<b>2</b> =20"	<b>3</b> = 3"	M = MNPT	Outlet	<b>6</b> = 316SS	@ 250 F	
Clamp SS Filter	7 = 7 Filters	<b>3</b> =30"	<b>4</b> = 4"	TC = Tri-Clamp				
Housing	<b>12</b> = 12 Filters	<b>4</b> =40"						
	<b>22</b> = 22 Filters							
	Example - 30"- 4	l round , 2"	Tri-Clamp I/O, O	pposite Side Outle	, 304SS, Buna N Ga	sket is GTCHB43	32TC2415PC	

Your Local Distributor:

### **ZenPure**

North & South Americas: ZenPure Americas, Inc www.zenpure.com Info-us@zenpure.com 703-335-9910 All Other Regions: ZenPure Corporation www.zenpure.com info@zenpure.com +86 571 2288 6800

Note- Not all options are available on all sizes of housings





Page 343

ZenPure

G68.5 Rev 2011.07 Tel.: +52 (55) 6273-4046 / 6273-4048 / 2465-1016



JAL