

Industrial Economy Filter Housing Multi-Round

The industrial economy stainless steel filter housings are constructed of 316L stainless steel for excellent resistance to corrosive chemicals and to ensure product purity. The housing is compatible with 10" to 40" filters elements to meet the needs of your application.

The housing can support 222 and 226 o-rings and Code F, double open-ended filters. A line of housings from 1 to 7 rounds are available to fit your flow rate needs. The unique design for Code F filters allows for cost saving and ease of installation.

The offset configurations allows rapid plumbing installation. The design of the housing provides for a positive seal with the filters, thereby preventing fluid bypass. The unique design for closure with fixed bolts and opti-clamp hold down to ensure maximum strength and ease of operation.

Customization of the housing is available.



Materials of Construction

Head: 316L Stainless Steel
 Bowl: 316L Stainless Steel
 Clamp: 304 Stainless Steel
 Center Post with Seal plate: 316L SS
 Vent/Drain Plug: 316L Stainless Steel
 O-Rings: Silicone, Viton or EPDM

Dimensions (nominal)

Lengths (in): 10, 20, 30 and 40

Connections - Offset

Inlet/Outlet : Tri Clamp, Flange, FNPT
 Vent/Drain : Tri Clamp, FNPT, Valve

Finish

Interior/Exterior: Bead Blast, Electropolished

Operating Conditions

Max operating pressure:
 125 psi (8.6bar) at 200°F (93°C)
 Test Pressure :
 165psi (11.4 bar) at 75°F (24°C)

Applications	
Acids	Ink Jets
Bases	Electronics
Solvents	Parts Cleaning
Fine Chemicals	Lacquers
Plating Solutions	Dyes

Industrial Economy Filter Housing Ordering Guide

Construction	Number of Filters	Length	Cartridge Code	Inlet/Outlet Fitting Size	Inlet/Outlet Fitting Style	Vent/Drain	Gasket Material	Interior/Exterior Finish
IE = Industrial Economy	3 = 3 Filters	1=10"	1 = DOE	1.5 = 1.5"	TC = Tri-Clamp	TC = 1/2" Tri-Clamp	E = EPDM	BBP = Bead Blast & Passivate EP = Electropolish
	5 = 5 Filters	2=20"	2 = Cup and Post	2 = 2"	F = Flange	N = 1/2" FNPT		
	6 = 6 Filters	3=30"	7 = 2-226		N = FNPT	V = 1/4" Valve		
	7 = 7 Filters	4=40"	8 = 2-222					

Example - 30"- 3 round for 222 filter, 2" Tri-Clamp I/O, 1/2" Tri-Clamp V/D, EPDM Gasket and Electropolished is **IE3382TCTCEEP**

Note- Not all options are available on all sizes of housings. See cut sheets for more detail.

Your Local Distributor:

ZenPure

North & South Americas:
 ZenPure Americas, Inc
 www.zenpure.com
 Info-us@zenpure.com
 703-335-9910

All Other Regions:
 ZenPure Corporation
 www.zenpure.com
 info@zenpure.com
 +86 571 2288 6800



ZenPure and PureFlo are registered trademarks of ZenPure Corporation or an affiliated company. Copyright 2003-2012 ZenPure or an affiliated company. All rights reserved.

G68 Rev 2013.01

Tel.: +52 (55) 6273-4046 / 6273-4048 / 2465-1016