

Sani-Lock[®] Standard Stock Items Hose Barb x Sani-Lock® TC & Butt Weld x Sani-Lock® TC

08BWT-08SL-SS

 $^{1\!/2"}$ Sani-Lock $^{\!\circ}$ Mini Tri-Clamp $^{\!\circ}$ x $^{1\!/2"}$ Butt Weld, 316SS

08HB-08SL-SS

¹/₂" Sani-Lock[®] Mini Tri-Clamp[®] x ¹/₂" HB, 316SS

12BWT-12SL-SS

3/4" Sani-Lock[®] Mini Tri-Clamp[®] x 3/4" Butt Weld, 316SS

12HB-12SL-SS

³/₄" Sani-Lock[®] Mini Tri-Clamp[®] x ³/₄" HB, 316SS

16BWT-16SL-SS

1" Sani-Lock[®] Tri-Clamp[®] x 1" Butt Weld, 316SS

16HB-16SL-SS

1" Sani-Lock[®] Tri-Clamp[®] x 1" HB, 316SS

24BWT-24SL-SS

1¹/₂" Sani-Lock[®] Tri-Clamp[®] x 1¹/₂" Butt Weld, 316SS

24HBL-24SL-SS

1¹/₂" Sani-Lock[®] Tri-Clamp[®] x 1¹/₂" HB, 316SS

32BWT-32SL-SS

2" Sani-Lock[®] Tri-Clamp[®] x 2" Butt Weld, 316SS

32HBL-32SL-SS

2" Sani-Lock[®] Tri-Clamp[®] x 2" HB, 316SS

Sani-Lock® Fitting/Adapter **Configuration Options**

Sanitary

BSN – Bevel Seat Nut

MBS - Male Bevel Seat, Threaded

FIL - Female I-line®

MIL - Male I-line®

JPF - John Perry Female

JPM – John Perry Male

OL – O-line

RTC - Reusable Tri-Clamp®

Pipe Thread (NPT)

FPT – Female Pipe Thread

MPT – Male Pipe Thread

Compression

CTA - Compression Tube Adapter

CTAFN – Compression Tube Adapter Ferrule and Nut

CTCFN – Compression Tube Connector

CTC – Compression Tube Connector

Cam and Groove

Consult factory at 973-579-2959 for other

Sani-Lock[®] Makes a Connection **Fast, Easy and Smart**

Sani-Lock® provides an easy point of attachment for hoses on process vessels, flow transfer panels, manifolds, and equipment that needs periodic maintenance including pumps, heat exchangers and filter housings. Sani-Lock® is great for a connection wherever a required scheduled break in the line is necessary for inspection or cleaning purposes. And because Sani-Lock® requires no tools, when working with components that are constantly removed or replaced such as tanks and vats, or systems that require constant breakdown and cleaning cycles, Sani-Lock® decreases down time and increases productivity.

SAVE TIME AND MONEY

One Sani-Lock® "quick connection" vs. multiple hinge clamp steps






360° rotation for easier installation. especially for hard to reach connections.











For a "quick-connection," Sani-Lock® can be welded to any fitting or adaptor, or, be added to any sanitary hose or sanitary pipe.



















FJIC - Female JIC

MUA – Male Union Adapter


150# Flanges


LJF – LAP Joint Flange

FCL - Female Cam-Lock

MCL - Male Cam-Lock

configurations and additional information.
























Distributed by:

RUBBER FAB technologies group

Rubber Fab Technologies Group

26 Brookfield Drive • Sparta, NJ 07871 phone: 973-579-2959 • fax: 973-579-7275

www.rubberfab.com

Rubber Fab Technologies Group is a member of:



International Association of



ISPE

