

# Pure Fit<sup>®</sup> SWP Wire-Reinforced Hose



*Pure-Fit<sup>®</sup> SWP is a high-pressure, platinum-cured silicone hose.*

## Pure-Fit<sup>®</sup> SWP Wire-Reinforced Hose

Pure-Fit<sup>®</sup> SWP platinum-cured silicone hose has a multi-layer construction and a 316 stainless steel helical wire reinforcement that offers ultimate flexibility in high pressure and vacuum rating situations.

Pure-Fit<sup>®</sup> SWP hose has an operating temperature range of -80°F (-62°C) to 500°F (260°C).

## Characteristics

The manufacturing process is carefully controlled from receiving through production and inspection. Lot traceability is readily accessible as batch numbers are assigned. All packages are identified by external labeling on both the bag and the high-quality, crush-proof box.

## Biocompatibility

Pure-Fit<sup>®</sup> SWP hose is manufactured from the finest grade of silicone materials and is fully tested to meet USP Class VI criteria.

## BIOPHARMACEUTICAL PRODUCTS

### Platinum-Cured Wire-Reinforced Silicone Hose

#### Features/Benefits

- Excellent bend radius
- Sterilizable
- Autoclavable
- Imparts no taste or odor
- Available in bulk or assemblies
- Pigmented outer cover available
- Available in 25-foot lengths
- Lot number traceability

#### Typical Applications

- Vacuum pump applications
- Pharmaceutical processing
- Biotechnology
- Bulk transfer
- Load cell

#### Connections

- Radially crimped 316L SS or non-metallic fittings
- Adapter connections

## Pure-Fit® SWP Hose Inventory Sizes

Part Number	ID Inches (mm)	OD Inches (mm)	Wall Inches	Max. Working Pressure PSI at 68°F	Burst Pressure PSI at 68°F	Minimum Bend Radius Inches	Weight Per Foot Lb.	Vacuum Rating IN. HG
HOSSWP-08	.500 (12.70)	.920 (23.37)	.210	150	600	1.5	.25	29.9
HOSSWP-12	.750 (19.05)	1.190 (30.23)	.220	125	500	2.5	.36	29.9
HOSSWP-16	1.000 (25.40)	1.450 (36.83)	.225	125	500	4.0	.48	29.9
HOSSWP-24	1.500 (38.10)	2.160 (54.86)	.330	125	500	5.5	1.00	29.9
HOSSWP-32	2.000 (50.80)	2.690 (68.33)	.345	100	400	7.0	1.25	29.9

## Sterilization Methods

- Autoclavable
- Radiation – up to 5.0 Mrad (50 Kilogray)
- Gas – Ethylene Oxide

**PURE-FIT® HOSE IS NOT INTENDED FOR USE AS AN IMPLANT MATERIAL**

Pure-Fit® is a registered trademark.

## BIOPHARMACEUTICAL PRODUCTS

*Come through clean.™*

### Saint-Gobain Performance Plastics

3910 Industrial Drive  
Beaverton, MI 48612  
Tel: (888) 387-0067  
Tel: (989) 435-9533  
Fax: (989) 435-2355



**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics tubing for all intended uses. Laboratory and clinical tests must be conducted in accordance with applicable regulatory requirements in order to determine the safety and effectiveness for use of tubing in any particular application.

For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risk, if any, including the risk of injury, loss or damage, direct or consequential, arising out of the use, misuse, or inability to use, this product. THIS WARRANTY IS IN LIEU OF THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. No deviation is authorized.

Saint-Gobain Performance Plastics Corporation assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to those products. All such advice is given and accepted at the buyer's risk.