

RUBBER FAB

technologies group

RFFDA



Food Grade FDA Nitrile Rubber Hose

TUBE: Smooth white nitrile

COVER: White nitrile rubber (abrasion and oil resistant)

REINFORCEMENT: Two polyester spirals with dual helix wire

TEMPERATURE: -40°F to 180°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
08RFFDA	0.50	0.97	1.50	200	FULL	0.35
12RFFDA	0.75	1.27	2.50	200	FULL	0.48
16RFFDA	1.00	1.56	3.00	200	FULL	0.75
24RFFDA	1.50	2.13	6.00	150	FULL	1.03
32RFFDA	2.00	2.63	7.00	150	FULL	1.44
40RFFDA	2.50	3.17	8.00	150	FULL	1.92
48RFFDA	3.00	3.69	9.00	150	FULL	2.43
64RFFDA	4.00	4.81	12.00	150	FULL	3.65

Features

- Ultra smooth inner bore
- Full vacuum
- Abrasion resistant cover
- Chemical and ozone resistant
- Will not impart taste or odor
- Static grounding available

Applications

- Oily food
- Potable water
- Sanitary suction and discharge
- Food and beverage transfer
- Dairy
- CIP pharmaceutical

Hose Certifications

- FDA 21 CFR 177.2600
- 3-A Sanitary Standards
- USDA
- Conforms to the construction criteria of the Grade A Pasteurized Milk Ordinance



26 Brookfield Drive • Sparta, New Jersey 07871

973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • www.rubberfab.com

Tel: +52 (55) 6273-4046 / 6273-4047 / 2465-1016