

RUBBER FAB

technologies group

RFSF SUPREME-FLEX



Smoothbore PTFE Lined Hose with Silicone Outer Cover

TUBE: Seamless white PTFE

COVER: White silicone

REINFORCEMENT: 304 stainless steel braid

TEMPERATURE: -100°F to 500°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
04RFSF	0.25	0.50	1.50	3250	FULL	0.13
06RFSF	0.37	0.65	2.00	2500	FULL	0.15
08RFSF	0.50	0.81	3.00	2000	FULL	0.18
12RFSF	0.75	1.02	8.20	1000	FULL	0.34
16RFSF*	1.00	1.36	12.00	1000	FULL	0.57

*Consult factory for availability

Features

- Superior flexibility
- High pressure rating
- Lining is smoothbore PTFE
- Excellent chemical resistance
- Non-stick contact surface will not contaminate contacted surfaces
- Autoclavable
- Steam cleanable at stated temperature and pressure rating
- Full vacuum rating
- Will not impart taste or odor
- Ultra smooth bacteria free tube

Applications

- Load cell
- CIP/SIP cleaning
- Filling equipment
- Sampling systems
- Fermentation lines
- Food and beverage processing
- Pharmaceutical processing
- Chemical transfer
- Sanitary transfer

Hose Certifications

- USP Class VI
- FDA 21 CFR 177.1550
- 3-A Sanitary Standards
- USDA



26 Brookfield Drive • Sparta, New Jersey 07871

973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • www.rubberfab.com

Tel: +52 (55) 6273-4046 / 6273-4047 / 2465-1016